

Датчик температуры NTC 10K**сопротивление при 25 °C, R25 = 10K Ω , Бета B25/85 = 3950K ±1%**

T, °C	R, KΩ	T, °C	R, KΩ	T, °C	R, KΩ	T, °C	R, KΩ
-40	340,9281	-3	38,2307	34	6,7996	70	1,7411
-39	318,8772	-2	36,294	35	6,5223	71	1,6826
-38	298,3978	-1	34,4668	36	6,2577	72	1,6264
-37	279,3683	0	32,7421	37	6,0053	73	1,5723
-36	261,6769	1	31,1138	38	5,7645	74	1,5203
-35	245,2212	2	29,5759	39	5,5345	75	1,4703
-34	229,9072	3	28,1229	40	5,315	76	1,4222
-33	215,6488	4	26,7496	41	5,1053	77	1,3759
-32	202,3666	5	25,4513	42	4,905	78	1,3313
-31	189,9878	6	24,2234	43	4,7136	79	1,2884
-30	178,4456	7	23,0618	44	4,5307	80	1,2471
-29	167,6783	8	21,9625	45	4,3558	81	1,2073
-28	157,6292	9	20,9218	46	4,1887	82	1,169
-27	148,246	10	19,9364	47	4,0287	83	1,1321
-26	139,4807	11	19,0029	48	3,8758	84	1,0965
-25	131,2888	12	18,1184	49	3,7294	85	1,0623
-24	123,6294	13	17,28	50	3,5893	86	1,0293
-23	116,4648	14	16,4852	51	3,4553	87	0,9974
-22	109,76	15	15,7313	52	3,3269	88	0,9667
-21	103,4829	16	15,0161	53	3,2039	89	0,9372
-20	97,6037	17	14,3375	54	3,0862	90	0,9086
-19	92,0947	18	13,6932	55	2,9733	91	0,8811
-18	86,9305	19	13,0815	56	2,8652	92	0,8545
-17	82,0877	20	12,5005	57	2,7616	93	0,8289
-16	77,5442	21	11,9485	58	2,6622	94	0,8042
-15	73,2798	22	11,4239	59	2,5669	95	0,7803
-14	69,2759	23	10,9252	60	2,4755	96	0,7572
-13	65,5149	24	10,451	61	2,3879	97	0,735
-12	61,9809	25	10	62	2,3038	98	0,7135
-11	58,6587	26	9,5709	63	2,2231	99	0,6927
-10	55,5345	27	9,1626	64	2,1456	100	0,6727
-9	52,5954	28	8,7738	65	2,0712	101	0,6533
-8	49,8294	29	8,4037	66	1,9998	102	0,6346
-7	47,2253	30	8,0512	67	1,9312	103	0,6165
-6	44,7727	31	7,7154	68	1,8653	104	0,599
-5	42,462	32	7,3954	69	1,8019	105	0,5821
-4	40,2841	33	7,0904				